

**INTRODUCING *NEW* ADDITIONS TO OUR**

**PLANETARY**

**HYDRAULIC**

**Winch  
Family**

- » High performance
- » Smoother dynamic braking
- » High efficiency piston motor
- » Meets API drum to cable ratio
- » Can be used in normal hoisting configuration or as single layer power-up/power-down arrangement



	<b>WN100</b>	<b>WN150</b>	<b>WN200</b>	<b>WN300</b>	<b>WN400</b>
<b>LAYER 1 PULL</b>	11344 lbs 50.5 kN	15081 lbs 67.0 kN	22501 lbs 100.0 kN	28373 lbs 126.0 kN	42928 lbs 191.0 kN
<b>LAYER 5 PULL</b>	9184 lbs 41.0 kN	12236 lbs 54.5 kN	17618 lbs 78.4 kN	21988 lbs 98.0 kN	32279 lbs 144.0 kN
<b>CABLE DIAMETER</b>	9/16 in 14 mm	5/8 in 16 mm	3/4 in 19 mm	7/8 in 22 mm	1 in 25 mm
<b>DRUM CAPACITY</b>	516 ft 157 m	551 ft 168 m	576 ft 176 m	624 ft 190 m	627 ft 191 m
<b>LAYER 1 MAX SPEED</b>	100 fpm 30 m/min	100 fpm 30 m/min	100 fpm 30 m/min	100 fpm 30 m/min	100 fpm 30 m/min
<b>FLOW @ MAX SPEED</b>	20 GPM 76 l/min	27 GPM 102 l/min	41 GPM 156 l/min	52 GPM 198 l/min	79 GPM 300 l/min
<b>RATED PRESSURE</b>	3250 psi 224 bar	3250 psi 224 bar	3250 psi 224 bar	3250 psi 224 bar	3250 psi 224 bar